

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

UTILITY PATENT APPLICATION TRANSMITTAL LETTER

09/495898 09/495898

BOX PATENT APPLICATION

Assistant Commissioner for Patents Washington, D.C. 20231

Sir:

Enclosed for filing is the utility patent application of <u>Rod Stambaugh</u> for <u>TRANSACTION</u> <u>PROCESSING USING INTERMEDIATE SERVER ARCHITECTURE</u>.

Also	enclosed are:
[X]	sheet(s) of [] formal [X] informal drawing(s);
[]	a claim for foreign priority under 35 U.S.C. §§ 119 and/or 365 is [] hereby made to _ filed in _ on _; [] in the declaration;
[]	a certified copy of the priority document;
[]	a General Authorization for Petitions for Extensions of Time and Payment of Fees;
[X]	A statement(s) claiming small entity status;
[X]	an Assignment document and Recordation Form Cover Sheet;
[]	an Information Disclosure Statement; and
[X]	Other: a return postcard.
[X]	An [X] executed [] unexecuted declaration of the inventor(s) [X] also is enclosed [] will follow.
[X]	Please amend the specification by inserting before the first line the sentenceThis application claims priority under 35 U.S.C. §§119 and/or 365 to U.S. Provisional Application Serial No. 60/167,552 filed in the United States on November 23, 1999 the entire content of which is hereby incorporated by reference
[]	A bibliographic data entry sheet is enclosed.



[X] The filing fee has been calculated as follows [] and in accordance with the enclosed preliminary amendment:

1 6 6 5 	NO. OF CLAIMS	it, 2	EXTRA CLAIMS	RATE	FEE	
Basic Applicati	on Fee				\$690.00 (101)	
Total Claims	26	MINUS 20 =	6	x \$18.00 (103)	108.00	
Independent Claims	2	MINUS 3 =	0	x \$78.00 (102)	0	
If multiple dep	endent claims a	re presented, add	\$260.00 (104)		0	
Total Applicati	on Fee				798.00	
If verified Statement claiming small entity status is enclosed, subtract 50% of Total Application Fee						
Add Assignment Recording Fee of \$40.00 (581) if Assignment document is enclosed 40.						
TOTAL APPI	LICATION FE	EE DUE	1	, , ,	\$439.00	

[]	This application is being filed without a filing fee.	Issuance of a Notice to File Missing
	Parts of Application is respectfully requested.	

[X] A check in the amount of \$ 439.00 is enclosed for the fee due.

[] Charge \$ _____ to Deposit Account No. 02-4800 for the fee due.

The Commissioner is hereby authorized to charge any appropriate fees under 37 C.F.R. §§ 1.16, 1.17 and 1.21 that may be required by this paper, and to credit any overpayment, to Deposit Account No. 02-4800. This paper is submitted in duplicate.

P.O. Box 1404

Alexandria, Virginia 22313-1404.

Respectfully submitted,

BURNS, DOANE, SWECKER & MATHIS, L.L.P.

Date: January 31, 2000

Michael J. Ure

Registration No. 23,089

P.O. Box 1404 Alexandria, Virginia 22313-1404 (650) 622-2300

Attorney 3 Docker No. <u>662657 666</u>
Applicant or Patentee: Rod Stambaugh
Application or Patent No.: <u>Unassigned</u>
Filed or Issued: Herewith
For: TRANSACTION PROCESSING USING INTERMEDIATE SERVER ARCHITECTURE
VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS (37 C.F.R. §§ 1.9(f) AND 1.27(c)) - SMALL BUSINESS CONCERN
I hereby declare that I am
 [] the owner of the small business concern identified below: [X] an official of the small business concern empowered to act on behalf of the concern identified below:
NAME OF CONCERN U.S. Wireless Data, Inc.
ADDRESS OF CONCERN 2200 Powell Street, Suite 450, Emeryville, California 94608
I hereby declare that the above-identified small business concern qualifies as a small business concern as defined in 13 C.F.R. § 121.12, and reproduced in 37 C.F.R. § 1.9(d), for purposes of paying reduced fees under Sections 41(a) and 41(b) of Title 35, United States Code, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average, over the previous fiscal year of the concern, of the persons employed on a full-time, part-time, or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control both.
I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention entitled <u>TRANSACTION PROCESSING USING INTERMEDIATE SERVER ARCHITECTURE</u> by inventor(s) <u>Rod Stambaugh</u> described in
[X] the specification filed herewith [] Application No, filed [] Patent No, issued
If the rights held by the above-identified small business concern are not exclusive, each individual, concern or organization having rights to the invention is listed below.* and no rights to the

If the rights held by the above-identified small business concern are not exclusive, each individual, concern, or organization having rights to the invention is listed below,* and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent inventor under 37 C.F.R. § 1.9(c), or by any concern that would not qualify as either a small business concern under 37 C.F.R. § 1.9(d) or a nonprofit organization under 37 C.F.R. § 1.9(e).

*NOTE: Separate verified statements are required from each named person, concern, or organization having rights to the invention averring to their status as small entities. (37 C.F.R. § 1.27.)

NAME			
ADDRESS			
ADDRESS	[] individual	[] small business concern	[] nonprofit organization
NAME			
ADDRESS	[] individual	[] small business concern	[] nonprofit organization
resulting in lo	ess of entitlement issue fee and a	to small entity status prior to	t, notification of any change in status o paying, or at the time of paying, the r the date on which status as a small
statements we punishable by Code; and the	made on informa vere made with th y fine or imprisonn nat such willful fa	ation and belief are believed he knowledge that willful falso ment, or both, under Section	own knowledge are true and that all to be true; and further that these statements and the like so made are 1001 of Title 18 of the United States ze the validity of the application, any statement is directed.
NAME OF PE	ERSON SIGNING	Scott Hamilton	
TITLE OF PE	RSON OTHER TH	AN OWNER Vice President S	ales & Marketing
ADDRESS O	F PERSON SIGNII	NG <u>2200 Powell Street, Suite</u>	450, Emeryville, California 94608
SIGNATURE	Sc	lex	DATE 1/27/00

TRANSACTION PROCESSING USING INTERMEDIATE SERVER ARCHITECTURE

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to transaction processing.

2. State of the Art

Transaction processing using a point-of-sale (POS) terminal is well-known. Other types of transactions may be non-financial. In the area of physical security, for example, terminals may be used by patrolmen to check in, producing evidence of their having been in the required place at the required time. Terminals may also be used in the healthcare industry, for example, to produce a record of what medical personnel have attended a patient at what times, or for myriad other purposes. Transaction processing is used generally herein to refer to the use of a transaction terminal to read, and possibly to write, a record-bearing medium such as a credit card, an ID card, a smart card, etc. The transaction terminal may use a contact or a contactless reading mechanism. In the case of smart cards, for example, a contactless radio interface of a type known in the art may be used.

The present invention will be described largely in terms of POS transactions, since this type of transaction is most familiar.

The approval and "settlement" process for POS transactions involves various parties and various steps. Briefly, the transaction terminal receives card data and purchase amount data and sends it through a communications network to a transaction processing center ("transaction processor," "front-end processor," or "processor"). The transaction processing center switches the transaction to an association (e.g., Visa, Mastercard, etc.) acting on behalf of an issuing bank. Assuming that the transaction is authorized by or on behalf of the issuing bank, an authorization message is sent back through the transaction processing center and the communications network to the transaction terminal. If the transaction is authorized, "capture" follows in which information from the successful authoriza-

tion is used to charge the authorized amount of money to the card. If goods are returned after the transaction has been captured, a "credit" is generated.

Settlement involves a merchant bank and an acquiring bank. The merchant bank has contracted with the merchant to enable the merchant to accept card transactions. The acquiring bank processes merchants's card transactions through the financial network on behalf of merchant banks (although in some instances the acquiring bank and the merchant bank may be the same). During settlement, captures and credits, usually accumulated into a "batch," are submitted from the merchant to the transaction processing center and on to the issuing and acquiring banks. As part of the settlement process, a "direction letter" may be sent to the U.S. Federal Reserve's Automated Clearing House (ACH) network, advising it as to what debits and credits need to occur in order to complete the transactions in the batch. The card issuer is debited the amount of the sale and the merchant's acquiring bank is credited a like amount. The merchant's acquiring bank then credits the merchant's checking account for the amount of the sale less any fees the merchant has agreed to pay for such service.

Referring to Figure 1, in the past, transaction terminals have typically been connected through a dial-up connection, through the PSTN (public switched telephone network) to a packet switched data network (e.g., an X.25 network) to a transaction processor. The transaction processor is connected in turn to various issuers (e.g., Visa, Mastercard, Discover, etc.) and to various acquiring banks.

Recently, a transaction terminal has been introduced that has a wireless modem—in particular a CDPD (cellular digital packet data) modem—that may be used to establish a connection to a CDPD network, bypassing the PSTN with its accompanying delays and charges. Such an arrangement is shown in Figure 2. The transaction terminal connects wirelessly to a wireless network such as a CDPD network. The CDPD network includes multiple Mobile Data Base Stations (MDBS) connected to a Mobile Data Intermediate Station (MDIS). The MDIS is

connected to a transaction processor via a Frame Relay connection. Frame Relay is used because it is much faster than an X.25 connection.

The system of Figure 2 suffers various disadvantages. In general, the system does not scale well to meet the needs of "distributed commerce" (or "mobile commerce"). Distributed commerce may be distinguished from e-commerce by a greater element of human involvement. Hence, whereas in e-commerce goods or services are ordered and paid for on-line, in distributed commerce, goods or services may be ordered in person and paid for by tender of a credit card or other non-cash payment medium, as opposed to the submission by the consumer (e.g., Web submission) of credit card information or the like. Examples of distributed commerce include such things as flagging a cab and, at the desired destination, paying by credit card, or phoning in an order for pizza and, at the time of delivery, paying by credit card. Other examples of distributed commerce include quick service restaurants, taxi and limousine services, delivery-based businesses, stadium concessions, stand-alone kiosks, and mobile businesses generally.

Like e-commerce, underlying characteristics of distributed commerce should be user convenience, greater satisfaction of demand, and vendor efficiency. However, various impediments hamper distributed commerce. Whereas the "plumbing" for e-commerce (i.e., the Web) has become almost universally established, the plumbing for distributed commerce remains *ad hoc*. A vendor must invest in terminal equipment and terminal software/firmware, enter into a subscription agreement with a wireless carrier, and, perhaps most importantly, ensure that a transaction processor is capable of receiving transactions through the wireless infrastructure, or is willing to invest to create such wireless capability. In the prior art system of Figure 2, for example, transaction processors are typically not equipped to handle Frame Relay traffic, requiring that a new "front end" be provided.

Furthermore, a vendor's equipment, representing a substantial investment,

may rapidly become obsolete. That is, in Figure 2, because intelligence is "hard-wired" into the transaction terminals, the transaction terminals themselves must be replaced, retrofitted or reprogrammed to accommodate new technologies (to accommodate ATM cards in addition to credit cards, to cite a historical example).

Also, in prior art systems, terminal management is cumbersome and laborintensive. Activating or deactivating a terminal is typically a laborious paper-based process that takes days or weeks. Keeping transaction terminals up and running is also problematic. The only way for a malfunctioning terminal to be identified and fixed is for it to be reported by the merchant, in response to which a service call is scheduled. Except in the most trivial cases, service usually entails replacing the transaction terminal and sending the faulty unit to a service center.

Moreover, in prior art systems, reporting is paper-based at intervals (e.g., monthly) in a fixed (not customizable) format.

Furthermore, today's hard-wired transaction terminals are relatively inefficient in their use of bandwidth.

Hence, although distributed commerce, like e-commerce, should be characterized by efficiency, flexibility and adaptability to rapid change, presently it is not.

What is needed, then, is a flexible distributed commerce system architecture that is highly efficient, that readily allows for new services to be offered, and that accommodates the existing transaction processor infrastructure.

SUMMARY OF THE INVENTION

The present invention, generally speaking, provides a scalable distributed commerce system architecture for transaction processing. The distributed commerce system takes advantage of the wireless infrastructure and the Web infrastructure to provide the capabilities of distributed (mobile) commerce along with many of the benefits of e-commerce. Preferably, the system is based on open standards, making possible ubiquitous "any-to-any" transaction processing in

which any compliant transaction terminal can communicate over any suitable wireless carrier and engage any transaction processor to successfully complete a wireless transaction. With the proliferation of wireless technologies, wireless transaction processing is expected to offer high-speed, reliable data transport, lower terminal costs, and lower wireless service costs (as compared to land-line charges). An important feature of the system is that an intermediate server receives data from a transaction terminal and processes the data. The processed data may then be forwarded to a transaction processor. The intermediate server may perform various types of processing, for example data format conversion, protocol conversion, etc. The server also makes possible various "value added services," e.g., ATM services, e-mail advertising services, customer attrition prevention services, customized reporting services, frequency and loyalty programs, etc. By linking the server to the Web, distributed commerce is able to incorporate the defining attributes of e-commerce, i.e., user convenience, greater satisfaction of demand, vendor efficiency and massive scalability. Parties using the system are able to obtain desired information in real time and take action (e.g., activate and deactivate terminals) in near-real time. The intermediate server makes possible the use of a "soft" transaction terminal, i.e., a "thin-client" (or pseudo thin-client) transaction terminal whose characteristics are determined in large part by the server. Tools are provided to effectively and efficiently manage provisioning, diagnostics, and reporting via a Web browser, enabling merchant acquires and card processors a fast and easy way to offer and manage a wireless transaction processing program with no systems development.

BRIEF DESCRIPTION OF THE DRAWING

The present invention may be further understood from the following description in conjunction with the appended drawing. In the drawing:

Figure 1 is a block diagram of a conventional transaction processing net-

work;

Figure 2 is a block diagram of a known transaction processing network using a wireless access point;

Figure 3 is a block diagram of a transaction processing network using a wireless access point and an intermediate server in accordance with one embodiment of the present invention;

Figure 4 is a screen display showing a transaction reporting feature of the system of Figure 3; and

Figure 5 is a diagram illustrating a card processor software architecture that may be used in the system of Figure 3.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to Figure 3, a block diagram is shown of a distributed commerce system in accordance with one embodiment of the present invention. The distributed commerce system is exemplified by the Wireless Express Payment Service (WEPSTM) network of the present assignee.

The WEPS network links together wireless terminals, WEPS servers, and transaction processor servers via established transport providers. WEPS servers are in turn linked to customers (e.g., acquirers, processor, and merchants) via the Internet. Collectively, the WEPS servers function as a value added translation gateway, enabling any supported terminal to engage in a transaction with any supported transaction processor.

The WEPS network is device neutral and supports all (or at least the most popular) wireless terminals (e.g., Intellect 9770, Lipman 2090, Keycorp K78, Tranz Enabler, etc.). Wireless terminals communicate via wireless networks, e.g., CDPD networks (AT&T, BAM, GTE, Ameritech, etc.), the American Mobile ARDIS network, BellSouth, etc. Currently, different wireless networks lead the market in different regions of the U.S. However, with the proliferation of wireless technologies, options for wireless communication will continue to multiply. The WEPS network is carrier neutral--i.e., a wireless terminal can use any desired

wireless network to communicate to the WEPS servers through the established Wide Area Network communications infrastructure. Wireless coverage may be of world-wide scope using satellite communications. In Figure 3 therefore, a satellite is illustrated as communicating with a satellite Network Operations Center (NOC) which in turn communicates with the established Wide Area Network communications infrastructure.

Although not illustrated in Figure 3, wired transaction terminals may also access the WEPS network through an Internet Service Provider (ISP) or through any or various means, e.g., Internet telephony, etc. In this manner, merchant having wired transaction terminals obtain the benefit of value added services offered by WEPS.

Referring still to Figure 3, wireless networks communicate with WEPS servers via established transport providers. WEPS servers communicate in turn with various transaction processors, again via established transport providers. As described in relation to the prior art, transaction processors are connected in turn to various issuers (e.g., Visa, Mastercard, Discover, etc.) and to various acquiring banks. In an exemplary embodiment, wired communications is provided between wireless networks, WEPS servers, and transaction processors using Frame Relay technology. Of course, the WAN "backbone" need not be wired (including optical) but, conceivably, may also be wireless.

Just as the WEPS network is device neutral and carrier neutral, the WEPS network is also transaction processor neutral--i.e., a transaction can be routed to any desired transaction processor, e.g., Paymentech, Nova, Maverick, Lynk Systems, First Data, Global/NDC, Buypass/EPS, etc. A suite of connectivity programs is used to perform format and protocol conversion as necessary between any supported terminal and any supported processor.

WEPS servers are situated at one or more data centers and, at each site, may reside on a Ethernet LAN or other local area network, forming an intranet.

The WEPS system may be based on any suitable intranet architecture may be two-tier, three-tier, etc. The servers are connected to a relational database management system (RDBMS) such as Oracle, for example. The database stores information for individual transaction terminals, identifying the type of terminal, the processor for that terminal, an appropriate connectivity program for enabling communication between the terminal and the transaction processor, etc. This information constitutes a terminal "profile." As described more fully hereinafter, the database also stores for transaction terminals thin-client "source programming," e.g., menu prompts, information to be printed, etc.

In addition to translation gateway services (i.e., any necessary message reformatting and protocol conversion), the WEPS servers perform other value added services such as terminal activation (IP activation in the case of CDPD, Radio ID activation in the case of ARDIS), remote diagnostics, transaction reporting, signature capture, e-mail, etc. Much of the power of the WEPS systems derives from databasing transaction processing information and, in a secure manner, making that information available to the "owners" of that information in real time via the Web, and from providing terminal deployment and management capabilities via the Web. These purposes are accomplished by connecting the WEPS servers to the Internet and providing a suite of database-driven Web tools. These tools may be custom tools, commercially-available tools, or a combination of both. To provide custom reporting capabilities, for example, a commercially-available tool, Crystal Reports, available from Seagate Software, may be used. Internet access allows acquirers, processors and merchants to manage terminals, obtain transaction reporting information, perform terminal diagnostics, etc. Figure 4 shows an exemplary screen display illustrating the transaction reporting feature.

In the WEPS system currently, terminal activation and deactivation typically require manual intervention by the wireless network operator. The WEPS server provides expedited messaging from the customer to the wireless network operator. In the future, tighter integration is expected to eliminate manual intervention entirely, resulting in entirely automated activation and deactivation.

Signature capture services enables the WEPS system to improve the chargeback and retrieval request management process that occurs when a card-holder disputes a charge on their statement by capturing and verifying signatures on wireless transactions. E-mail advertising provides a way for a merchant acquirer to quickly and effectively broadcast to merchants promotions about the acquirer's new products and supplies. The range of value added services that may be offered is unlimited.

Additional examples of WEPS value added services include ATM services, customer attrition prevention, and frequency and loyalty programs. Through ATM services, WEPS servers can provide transaction processing benefits and services to wireless ATM machines. In the case of customer attrition prevention, this service would require the merchant to contact their current acquirer in order to obtain certain password information that would allow the terminal to be switched to another processor. This authorization feature would notify the current acquirer about an unhappy merchant and give the acquirer the opportunity to resolve any problems. Given the intranet/Internet architecture of the WEPS system, incentive programs can be easily implemented at the POS terminal and processed by the WEPS system in order to encourage additional wireless transactions.

Apart from POS applications, the WEPS system has the capability to handle any transaction-based data from any wireless network. Thus, the system can accommodate non-payment applications such as medical claims processing, collecting and processing telemetry data for oil, gas and other meter reading applications, coupling dispatch and "panic button" communications with in-vehicle payment processing applications, etc.

In operation of the system of Figure 3, in the case of POS transactions, a WEPS-certified wireless POS terminal transmits card data, merchant data and

transaction amount data to the wireless network. The wireless network then forwards the data packets to a WEPS server, via frame relay for example. The WEPS server "looks" at the transaction (based on the terminal profile) and determines if protocol conversion, message reformatting, or any other data manipulation is required. If the data needs to be manipulated, the WEPS server performs such functions and then sends the resulting data to the designated transaction processor, again via frame relay for example. If no manipulation is required, the data is merely passed through the WEPS server "as is" in store-and-forward fashion. Whether the transaction needs manipulation or not, pertinent data is "stripped" and sent to the WEPS database, where real-time reports are created for the acquirer/merchant. These reports can be accessed on a real-time basis via any Web browser.

The transaction processor receives the transaction from WEPS, via frame relay for example, and switches it to the appropriate card issuer for authorization. Once authorized, the data packet (which now includes an authorization code) is sent back to the transaction processor, which then forwards it back to the WEPS server. If needed, the protocol conversion/reformatting manipulation process is reversed. The authorization code is added to the WEPS database, and the completed transaction data is sent back to the wireless terminal via frame relay (or other suitable transport mechanism) and the wireless network.

The amount of data manipulation required by the WEPS system is dependent on the type of transaction terminal and the identity of the transaction processor. In the simplest case, as in Figure 2, the transaction terminal and the transaction processor are capable of communicating "directly" with one another, i.e., through the combination of wireless and wired transport mechanism but without any translation. In this instance, the WEPS system simply operates in store-and-forward mode. A more difficult case is presented where the transaction terminal assumes one format (e.g., Global) but the transaction is to be routed to a transaction proces-

sor that uses a different format (e.g., Maverick). The Global and Maverick formats are described in Appendix A and Appendix B, respectively. In this instance, a first connectivity module (e.g., Global receive module) "parses" the incoming message into its constituent elements. A second connectivity module (e.g., Maverick send module) reassembles some or all of those elements, and possibly other elements stored in the WEPS database, into the appropriate format to send to the transaction processor for that transaction as indicated in the terminal profile stored in the WEPS database.

Message formatting by the server allows for low latency and fast response time. For example, the UDP communications protocol may be used on a network segment between the transaction terminal and the server. The UDP protocol is low overhead and therefore faster than more complex protocols such as X.25 or TCP. In addition, the server may store information about the various transaction terminals and use this information to "fill in" various information fields prior to transmission to the transaction processor across the second network segment. These fields need not be transmitted on the first network segment from the transaction processor to the server, resulting in higher-speed operation.

Because of the low latency between the transaction terminal and the server, the transaction terminal and the server can function as client/server. Client/Server is primarily a relationship between processes running on separate machines. The server process is a provider of services. The client is a consumer of services. In essence, client/server provides a clean separation of function based on the idea of service.

In the context of a transaction processing system, adherence to a client/server model provides several important advantages. The transaction terminal, instead of being a fairly sophisticated computer, can instead be a relatively "dumb" terminal, relying on the server for "transaction intelligence." A great economy is therefore achieved. Of perhaps even more importance, adaptability is achieved. Changes to transaction intelligence can be deployed in one place, on the server, without requiring field modifications to an installed base of transaction terminals.

"Thin client," in one sense, implies a dumb terminal that operates in request/reply mode. In the case of a transaction terminal, data representing hardware inputs would be mapped to corresponding replies. For example, in response to an initial card swipe (request), the reply from the server might be "ENTER AMOUNT," and so forth. In the case of a transaction terminal running off of line power, such an arrangement would be satisfactory (assuming communications latency were sufficiently low to avoid user irritation). In the case of a battery-power transaction terminal, however, such a true thin-client mode of operation consumes excessive power.

In an exemplary embodiment, a thin-client specification for WEPS compliant terminal devices is provided. Terminal devices manufacturers desiring to take advantage of the powerful features of the WEPS system can do so by making their terminal equipment WEPS compliant. The specification standardizes the terminal device message format, and over time (as the proportion of WEPS compliant terminals increases) is expected to greatly simplify the translation function required to be performed by the WEPS server.

The WEPS thin-client specification provides for one or both of a "pseudo" thin-client mode of operation and a true thin-client mode of operation. Where both modes are provided, two separate "menus" are defined, mapping hardware inputs to corresponding replies. A first menu governs operation in pseudo thin-client mode. In this mode, replies are downloaded from the server in advance and stored locally in the transaction terminal. Hence, in response to a card being swiped, instead of transmitting card data immediately to the server and waiting for the server's reply, such as "ENTER AMOUNT," the terminal device retrieves the reply (previously downloaded from the server) from its own local memory. This manner of operation preserves the battery life of the transaction terminal. The

"reply" may be output to a display, output to a printer, used to control some aspect of terminal operation, etc.

Despite the menu and replies being stored in the transaction terminal, no loss of flexibility is suffered--the menu can be changed at any time by the server establishing a connection with the terminal and sending new menu information. A routine within the terminal parses the new menu information and stores various menu elements in appropriate locations within a non-volatile (NV) memory (e.g., flash memory) of the terminal. Note that menu information is defined on a *per terminal basis*. Thus, in the case of a large merchant having a large number of terminals within different departments, the terminals may all be of the same type--(or may be of different types)-- but the programs of those terminals may vary from department to department, for example.

A second (presumably less-used) menu governs operation in true thin-client mode. In this mode, responses are not stored locally but are sent through the network from the server. This arrangement avoids incurring the cost of local NV storage for lesser-used options.

Referring to Figure 5, the architecture of card processor software that may be used in the system of Figure 3 is shown. In an exemplary embodiment, the software is *service*-based. A socket listener service listens for messages from terminal devices. When the service is begun, database information is stored in memory to enable rapid processing. Changes in the data cause the database to be updated.

When a message is received (DATA ARRIVAL), an execution thread is begun (BEGIN THREAD), causing objects (in this example, COM objects) to be instantiated for the purpose of processing the message. First, the IP address/terminial ID (TID) is validated against the database information stored in memory. If the IP/TID is not valid, then the packet is dropped. Otherwise, an object is invoked to perform conversion of the data to the appropriate format based on the terminal profile. Depending on which transaction processor is designated, a corresponding

conversion object is invoked In the illustrated example, Paymentech is assumed to be the transaction processor of choice. Therefore, the incoming data is converted to Paymentech format and sent to Paymentech. A card validation process ensues, involving, e.g., Paymentech and one or more other downstream processors (e.g., Visa).

If validation fails, then error processing ensues in which an entry is created in an error log. The error log may be set up to send email notification of critical events.

If validation succeeds, an object is invoked to send back to the terminal a validation response in the appropriate format. Latency is reduced by saving response information to the database only after the response has been sent to the terminal. The execution thread is then killed.

If an error occurs during the course of sending the response back to the terminal, then error information is returned and logged in the event log.

As has been detailed in the foregoing description, the present transaction processing system provides for ubiquitous "any-to-any" wireless (as well as wired) transaction processing capability, enabling penetration of new markets such as fast food, mobile merchants, transportation, etc. The resulting mobility and flexibility allows business to be conducted anywhere, with fast transaction times and savings in communication costs. Wireless access may occur through any wireless data network. The system inter-operates with an unlimited variety of wireless terminal equipment, including handheld units, countertop units, mobile units and new high speed terminal devices. Application flexibility is provided through the use of a thin-client or pseudo thin-client application in the terminal devices. Web accessibility allows for easy terminal set-up, on-line activation and provisioning, remote diagnostic capabilities, and real-time transaction reporting, in addition to myriad other value added card services. The system is always on-line, allowing for

real-time, up-to-the-minute reporting capability.

It will be appreciated by those of ordinary skill in the art that the invention can be embodied in other specific forms without departing from the spirit or essential character thereof. The presently disclosed embodiments are therefore considered in all respects to be illustrative and not restrictive. The scope of the invention is indicated by the appended claims rather than the foregoing description, and all changes which come within the meaning and range of equivalents thereof are intended to be embraced therein.

APPENDIX A:

Global Payment Systems--Host Authorization and ECD Message Specification

The message contains the following information:

STX	MSG ID	VERSION	ROUTING DATA	FS	BANK ID	MERCH ID	FS	TERM TYPE	FROC. CODE	
FS	ENTRY MODE	FS	MANUAI	SWIPE: L: ACCT	TRACK DATA	XP DATE	FS	AMOUNT 1	FS	
	AMOUT 2	nt fs	ACQ REF DATA	FS	AVS INFO	FS	MKT DATA	FS	Photographs	
		SHIFT ID	FS C	LERK ID	FS	MER TYPE	ETX	LRC		

Field	Description
STX	Start of Text Indicator. Required for dial-up. Not used on leased lines.
Message ID	Required. Always * (literal *).
Version	Required. Level version of the message (02).
Routing Data	Optional user-definable data. Echoed in Global's response unaltered.
FS	Field Separator
Bank ID	Required. Identifies 6-digit Bank ID assigned by Global.
Merchant ID	Required. Unique number identifying merchant device.
FS	Field Separator
Terminal Type	Required. Global-assigned code indicating type of POS device.
Processing Code	Required. Code that designates processing instructions.
FS	Field Separator
POS Entry Mode	Required. Code indicating POS device characteristics.
FS	Field Separator
Swipe: Track Data	Conditional. Required if swiped. The data encoded on Track 1 or Track 2.
Manual: Account Number	Conditional. Required if manually keyed. The account number.
Manual: FS	Conditional. Required if manually keyed. Field Separator
Manual: Expiration Date	Conditional. The expiration date. Present on keyed transactions (if available).
FS	Field Separator

Field	Description
Amount 1	Required. The total amount of the transaction, including Amount 2.
F8	Field Separator
Amount 2	Optional. Additional amount already included in Amount 1. For reporting purposes. (example, tip amount)
FS	Field Separator .
Acquirer Reference Data	Conditional. Data varies by card type and market. Poleste Appendix B 10 (1988)
FS	Field Separator
AVS Information	Conditional. 9 character zip and 20 character street address.
FS -	Field Separator
Market Data	Required for signature capture transactions. Defined by market. Required for signature capture transactions. Sub-field y contains the Transaction Reference Number, which is used to identify signature capture data throughout the life cycle of the transaction.
FS	Field Separator
Shift ID	Optional. Shift ID number.
FS	Field Separator
Clerk ID	Optional. Clerk ID number.
FS	Field Separator
Merchant Type	Optional. Merchant Category Code.
ETX.	End of Text Indicator. Required for dial-up. Not used on leased lines.
LRC	Longitudinal Redundancy Check Character. Required for dial-up. Not used on leased lines.

APPENDIX B:

Maverick International--Maverick Protocol

Authorization requests using Maverick's proprietary authorization request record "M" will receive the standard Visa 2nd generation "L" response record. Terminals using Maverick's "M" authorization request format will capture the Authorization Code (field 9) and the Retrieval Reference Number (field 14) for settlement, but may capture other fields as necessary (such as the Transaction ID and Validation Code) for performing incremental authorizations.

Field name descriptions are explained by section in this document. Data format designations: A= Alphanumeric, N= Numeric.

Field Number	Field Name	me Data Format		Section	Example
1 Trumber	Record Format	A	Length	4.1	200
2	Application Type	A	1	4.1	<u>M</u>
3	Message Delimiter	Ā	1	<u> </u>	У п
4	Acquirer Bin		6	4.3	•
5	Terminal Number	N		4.4	"123456"
6		N	-10-	4.5	"999999901"
	Field Separator	A	1	4.6	<fs> or HEX 1C</fs>
7	Transaction Sequence Number	N	4	4.7	0001
8	Transaction Code	Α	2	4.8	"54"
9	Cardholder ID Code	Α	l	4.9	"@"
10	Account Data Source Code	A	1	4.10	D
11	Customer Data Field	A	1-80	4.11	JOHNSMITH
12	Field Separator	Α	1	4.6	<fs> or HEX 1C</fs>
13	Address Verification	See Section	See	4.12	1234MAINSTREET123456789
	OR	4.12	Section		OR
	Authorization Code		4.12		123456 (Auth Code)
14.1	Field Separator	Α	1	4.6	<fs> or HEX 1C</fs>
14.2	Transaction	A	0 to 4	4.13	
	Processing Indicators				
15	Field Separator	A	l	4.6	<fs> or HEX 1C</fs>
16	Transaction Amount	N	0 to 12	4.14	
17	Field Separator	Α	1	4.6	<fs> or HEX 1C</fs>
18 .	Secondary Amount	N	0 to 12	4.15	
19	Field Separator	A	1	4.6	<fs> or HEX 1C</fs>
20	Market Specific Data	Α	0 or 4	4.16	
21	Field Separator	. A	1	4.6	<fs> or HEX 1C</fs>
22	Informational Data	A	0-60	4.17	
23	Field Separator	Α	1	4.6	<fs> or HEX 1C</fs>
24	Original Reference Number	N	0 or 12	4.18	
25	Field Separator	A	1	4.6	<fs> or HEX 1C</fs>
26	Purchasing Card Data	A	0-17	4.19	
27	Field Separator	A	ı	4.6	<fs> or HEX 1C</fs>
28	Free Form Data	. A	0-45	4.20	
29	Field Separator	: <u>A</u>	1	4.6	<fs> or HEX 1C</fs>

What is claimed is:

1. A method of transaction processing, comprising:

a user bringing a record-bearing medium in operational proximity to a transaction terminal to allow the transaction terminal to receive information from the record-bearing medium;

the transaction terminal accessing a communications network and sending first transaction information across the communications network;

receiving and processing the first transaction information at a server; and

the server sending second transaction information to a further destination.

- 2. The method of Claim 1, wherein the further destination is a transaction processor installation.
- 3. The method of Claim 1, wherein the transaction terminal wirelessly accesses the communications network.
- 4. The method of Claim 1, wherein the transaction terminal includes an output device, and the server controls presentation of information to a user through the output device.
 - 5. The method of Claim 4, wherein the output device is a display.
- 6. The method of Claim 1, wherein the first transaction information is transported using a first protocol, and the second transaction information is transported using a second different protocol.
- 7. The method of Claim 6, wherein the first protocol has lower overhead than the second protocol.

- 8. The method of Claim 1, wherein the first transaction information is in a first format, and the second transaction information is in a second different format, further comprising the server reformatting the transaction information from the first format to the second format.
- 9. The method of Claim 8, wherein the first format is more compact than the second format.
- 10. The method of Claim 9, wherein the server stores locally information about various transaction terminals and uses this information to reformat the transaction information from the first format to the second format.
- 11. The method of Claim 1, further comprising the server capturing and storing transaction information.
- 12. The method of Claim 11, further comprising providing customers secure access to their respective transaction information via a Web browser.
- 13. The method of Claim 12, wherein transaction information is made available to customers in real time as it is captured and stored by the server.
 - 14. The method of Claim 1, further comprising:
 a customer communicating via the Web to the server a desired action with respect to a transaction terminal; and

the server communicating with one of a wireless network and a transaction terminal to carry out the desired action.

15. The method of Claim 14, wherein the desired action is terminal activation/deactivation.

- 16. The method of Claim 14, wherein the desired action is terminal diagnostics.
 - 17. A transaction processing network, comprising:

multiple transaction terminals wherein a user bringing a recordbearing medium in operational proximity to a transaction terminal to allow the transaction terminal to receive information from the record-bearing medium;

a server;

a first network segment linking multiple transaction terminals to the server; and


a second network segment linking the server to multiple further destinations.


- 18. The apparatus of Claim 17, wherein at least one of the further destinations is a transaction processor installation.
- 19. The apparatus of Claim 17, wherein the transaction terminal comprises a wireless data communications device.
- 20. The apparatus of Claim 17, wherein the transaction terminal includes an output device, and the server controls presentation of information to a user through the output device.
 - 21. The apparatus of Claim 20, wherein the output device is a display.
- 22. The apparatus of Claim 17, wherein first transaction information is transported across the first network segment using a first protocol, and second different transaction information is transported across the second network segment using a second different protocol.


- 23. The apparatus of Claim 22, wherein the first protocol has lower overhead than the second protocol.
- 24. The apparatus of Claim 22, wherein the first transaction information is in a first format, and the second transaction information is in a second different format, and the server reformats the transaction information from the first format to the second format.
- 25. The apparatus of Claim 24, wherein the first format is more compact than the second format.
- 26. The method of Claim 25, wherein the server stores in a local store information about various transaction terminals and uses this information to reformat the transaction information from the first format to the second format.

ABSTRACT OF THE DISCLOSURE

The present invention, generally speaking, provides a scalable distributed commerce system architecture for transaction processing. The distributed commerce system takes advantage of the wireless infrastructure and the Web infrastructure to provide the capabilities of distributed (mobile) commerce along with many of the benefits of e-commerce. Preferably, the system is based on open standards, making possible ubiquitous "any-to-any-to-any" transaction processing in which any compliant transaction terminal can communicate over any suitable wireless carrier and engage any transaction processor to successfully complete a wireless transaction. With the proliferation of wireless technologies, wireless transaction processing is expected to offer high-speed, reliable data transport, lower terminal costs, and lower wireless service costs (as compared to land-line charges). An important feature of the system is that an intermediate server receives data from a transaction terminal and processes the data. The processed data may then be forwarded to a transaction processor. The intermediate server may perform various types of processing, for example data format conversion, protocol conversion, etc. The server also makes possible various "value added services," e.g., ATM services, e-mail advertising services, customer attrition prevention services, customized reporting services, frequency and loyalty programs, etc. By linking the server to the Web, distributed commerce is able to incorporate the defining attributes of e-commerce, i.e., user convenience, greater satisfaction of demand, vendor efficiency and massive scalability. Parties using the system are able to obtain desired information in real time and take action (e.g., activate and deactivate terminals) in near-real time. The intermediate server makes possible the use of a "soft" transaction terminal, i.e., a "thin-client" (or pseudo thin-client) transaction terminal whose characteristics are determined in large part by the server. Tools are provided to effectively and efficiently manage provisioning, diagnostics, and reporting via a Web browser, enabling merchant acquires and card processors a








🚬 nauti i eut. eus. est. es armeus nemar nemar nepallmainz, asp (1 erminall)=415/61999994203 - Microsoft Internet Explorer

をである。



F16-5

COMBINED DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY Attorney's Docket No.									
(Includes Refe	erence to Provision	onal and PCT International Applic	ations)	032397-009					
As a below named inventor, I hereby declare that: My residence, post office address and citizenship are as stated below next to my name; I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: TRANSACTION PROCESSING USING INTERMEDIATE SERVER ARCHITECTURE									
the sp	pecification of wl	nich (check only one item below):	:						
$\overline{\mathbf{x}}$	is attached here	to.							
	was filed as Un	ited States application							
		• •							
		······································							
	and was amende								
÷	on	(if applicable).						
	was filed as PCT international application								
19 190 190 10 190	Number								
- 100 - 100									
	and was amende	ed							
	on	((if applicable).						
(i) I hereby stat	e that I have rev any amendment	iewed and understand the contents referred to above.	s of the above-identified specificat	tion, including the claims, as					
I acknowled		sclose to the Office all information	n known to me to be material to p	atentability as defined in Title					
America list international	s certificate or of ed below and had application(s) de	any PCT international applications also identified below any foreign at least one country of	States Code, §119 (a)-(e) of any n(s) designating at least one count gn application(s) for patent or invertian the United States of Amern(s) of which priority is claimed:	try other than the United States of entor's certificate or any PCT					
PRIOR FORE	IGN/PCT APPL	ICATION(S) AND ANY PRIOR	ITY CLAIMS UNDER 35 U.S.(C. §119:					
	NTRY cate "PCT")	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 35 U.S.C. §119					
				_Yes _No					
				_ Yes _ No					
				_ Yes _ No					
				_ Yes _ No					
				Yes No					
I hereby claim	the benefit unde	er Title 35, United States Code §	119(e) of any United States provis						
			•						
	67,552		November 23, 1999						
(Appl	lication Number)	(F	Filing Date)						
(Appl	ication Number)		Filing Date)						

COMBINED DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY (CONTINUED) (Includes Reference to Provisional and PCT International Applications)

Attorney's Docket No.

032397-009

I hereby claim the benefit under Title 35, United States Code, §120 of any United States applications(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose to the Office all information known to me to be material to the patentability as defined in Title 37, Code of Federal Regulations §1.56, which became available between the filing date of the prior application(s) and the national or PCT international filing date of this application:

PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT UNDER 35 U.S.C. 120:

	STA	STATUS (check one)			
U.S. APPLICATION NUM	1BER	U.S. FILING DATE	PATENTED	PENDING	ABANDONE
PCT A	APPLICATIONS DESIGNATING	THE U.S.			
PCT APPLICATION NO.	PCT FILING DATE	U.S. APPLICATION NUMBERS ASSIGNED (if any)			
12.					
17. 10. 10.					ļ
155 155					

Hereby appoint the following attorneys and agent(s) to prosecute said application and to transact all business in the Patent and Trademark Office connected therewith and to file, prosecute and to transact all business in connection with international applications directed to said invention:

n de	
William L. Mathis	17,337
Robert S. Swecker	19,885
Platon N. Mandros	22,124
Benton S. Duffett, Jr.	22,030
Norman H. Stepno	22,716
Ronald L. Grudziecki	24,970
Frederick G. Michaud, Jr.	26,003
Alan E. Kopecki	25,813
Regis E. Slutter	26,999
Samuel C. Miller, III	27,360
Robert G. Mukai	28,531

R. Danny Huntington	27,903
Eric H. Weisblatt	30,505
James W. Peterson	26,057
Teresa Stanek Rea	30,427
Robert E. Krebs	25,885
William C. Rowland	30,888
T. Gene Dillahunty	25,423
Patrick C. Keane	32,858
Bruce J. Boggs, Jr.	32,344
William H. Benz	25,952
Peter K. Skiff	31,917
Richard J. McGrath	29,195
Matthew L. Schneider	32,814
Michael G. Savage	32, 596

Gerald F. Swiss Michael J. Ure 33,089 Charles F. Wieland III 33,096 Bruce T. Wieder 33,815 Todd R. Walters 34,040 Ronni S. Jillions 31,979 Harold R. Brown III 36,341 Allen R. Baum 36,086 Steven M. du Bois 35,023 Brian P. O'Shaughnessy 32,747

21839

and:

r fi

Address all correspondence to:

George A. Hovanec, Jr. James A. LaBarre

E. Joseph Gess



21839

Robert E. Krebs

BURNS, DOANE, SWECKER & MATHIS, L.L.P.

P.O. Box 1404

Alexandria, Virginia 22313-1404

Address all telephone calls to: Michael J. Ure

at (650) 622-2300.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

COMBINED DECLARATION FOR PATENT APPLICATION AND POW	Attorney's Docket No. 032397-009			
FULL NAME OF SOLE OR FIRST INVENTOR	SIGNATURE	DATE		
Rod Stambaugh	KOTA M	1-24-2000		
RESIDENCE	1 0 // 1 //	CITIZENSHIP		
1123 Western Avenue, Mill Valley, California 94941, United States of America POST OFFICE ADDRESS US US				
Same as above		h . mm		
FULL NAME OF SECOND JOINT INVENTOR, IF ANY	SIGNATURE	DATE		
RESIDENCE		CITIZENSHIP		
POST OFFICE ADDRESS				
FULL NAME OF THIRD JOINT INVENTOR, IF ANY	SIGNATURE	DATE		
RESIDENCE		CITIZENSHIP		
POST OFFICE ADDRESS				
FULL NAME OF FOURTH JOINT INVENTOR, IF ANY	SIGNATURE	DATE		
RESIDENCE		CITIZENSHIP		
DOCUM OPPIGE ADDRESS				
POST OFFICE ADDRESS				
FULL NAME OF FIFTH JOINT INVENTOR, IF ANY	SIGNATURE	DATE		
RESIDENCE		CITIZENSHIP		
POST OFFICE ADDRESS				
FULL NAME OF SIXTH JOINT INVENTOR, IF ANY	SIGNATURE	DATE		
RESIDENCE		CITIZENSHIP		
POST OFFICE ADDRESS				
FULL NAME OF SEVENTH JOINT INVENTOR, IF ANY	SIGNATURE	DATE		
RESIDENCE		CITIZENSHIP		
POST OFFICE ADDRESS				
FULL NAME OF EIGHTH JOINT INVENTOR, IF ANY	SIGNATURE	DATE		
RESIDENCE		CITIZENSHIP		
POST OFFICE ADDRESS				
FULL NAME OF NINTH JOINT INVENTOR, IF ANY	SIGNATURE	DATE		
RESIDENCE		CITIZENSHIP		
POST OFFICE ADDRESS				